

SELF-HOST > インストール&デプロイガイド > ヘルム

rawManifest ファイルを追加します

ヘルプセンターで表示:

<https://bitwarden.com/help/add-rawmanifest-files/>

rawManifestファイルを追加します

Bitwarden自己ホスト型Helm Chartは、インストール前またはインストール後に他のKubernetesマニフェストファイルを含めることができます。これを行うには、チャートの `rawManifests` セクションを更新してください。

Traefik IngressRouteの例

例えば、KubernetesのIngressコントローラーの代わりにTraefikのIngressRouteをインストールするには、以下を追加します:

Note

この例では、`my-values.yaml` ファイル内の `general.ingress.enabled` :
でもイングレスコントローラーを無効にする必要があります。

Bash

```
rawManifests:
  preInstall: []
  postInstall:
    - apiVersion: traefik.containo.us/v1alpha1
      kind: Middleware
      metadata:
        name: "bitwarden-self-host-middleware-striprefix"
      spec:
        stripPrefix:
          prefixes:
            - /api
            - /attachments
            - /icons
            - /notifications
            - /events
            - /scim
            ##### NOTE: Admin, Identity, and SSO will not function correctly with path strip middlew
are
    - apiVersion: traefik.containo.us/v1alpha1
      kind: IngressRoute
      metadata:
        name: "bitwarden-self-host-ingress"
      spec:
        entryPoints:
          - websecure
        routes:
          - kind: Rule
            match: Host(`REPLACEME.COM`) && PathPrefix(`/`)
            services:
              - kind: Service
                name: bitwarden-self-host-web
                passHostHeader: true
                port: 5000
          - kind: Rule
            match: Host(`REPLACEME.COM`) && PathPrefix(`/api/`)
```

```
services:
  - kind: Service
    name: bitwarden-self-host-api
    port: 5000
middlewares:
  - name: "bitwarden-self-host-middleware-stripprefix"
- kind: Rule
match: Host(`REPLACEME.COM`) && PathPrefix(`/attachments/`)
services:
  - kind: Service
    name: bitwarden-self-host-attachments
    port: 5000
middlewares:
  - name: "bitwarden-self-host-middleware-stripprefix"
- kind: Rule
match: Host(`REPLACEME.COM`) && PathPrefix(`/icons/`)
services:
  - kind: Service
    name: bitwarden-self-host-icons
    port: 5000
middlewares:
  - name: "bitwarden-self-host-middleware-stripprefix"
- kind: Rule
match: Host(`REPLACEME.COM`) && PathPrefix(`/notifications/`)
services:
  - kind: Service
    name: bitwarden-self-host-notifications
    port: 5000
middlewares:
  - name: "bitwarden-self-host-middleware-stripprefix"
- kind: Rule
match: Host(`REPLACEME.COM`) && PathPrefix(`/events/`)
services:
  - kind: Service
    name: bitwarden-self-host-events
    port: 5000
middlewares:
```

```
- name: "bitwarden-self-host-middleware-striprefix"
- kind: Rule
match: Host(`REPLACEME.COM`) && PathPrefix(`/scim/`)
services:
  - kind: Service
    name: bitwarden-self-host-scim
    port: 5000
middlewares:
  - name: "bitwarden-self-host-middleware-striprefix"
##### NOTE: SSO will not function correctly with path strip middleware
- kind: Rule
match: Host(`REPLACEME.COM`) && PathPrefix(`/sso/`)
services:
  - kind: Service
    name: bitwarden-self-host-sso
    port: 5000
##### NOTE: Identity will not function correctly with path strip middleware
- kind: Rule
match: Host(`REPLACEME.COM`) && PathPrefix(`/identity/`)
services:
  - kind: Service
    name: bitwarden-self-host-identity
    port: 5000
##### NOTE: Admin will not function correctly with path strip middleware
- kind: Rule
match: Host(`REPLACEME.COM`) && PathPrefix(`/admin`)
services:
  - kind: Service
    name: bitwarden-self-host-admin
    port: 5000
tls:
  certResolver: letsencrypt
```